
MEGA M-55 Specifications

- 1/4" Plunger Pump for 6000 PSI (.018in³ per impulse, max.)
- 3/8" Plunger Pump for 3500 PSI (.041in³ per impulse, max.)
- Rugged Sheet Metal Reservoirs in 3, 4, 8, 12, 16, 20, 24, 32 and 40 pint sizes. Maximum 28 feeds in 40 pint.
- Suitable for use with petroleum or synthetic lubricants.
- Complete Lubricators available to replace McCord and Lincoln units.

Optional Features

- Cast Aluminum Reservoirs in 4, 8, 16 and 24 pint sizes.
- Pressurized Suction Pumps.
- Automatic Oil Level Controls.
- Low Level Switches.
- Shaft Rotation/Low Level Alarms.
- Oil Heaters with thermostats.
- Multi-Compartment Reservoirs for 2 or more lubricants.
- Electric Motor Drive.

Accessories

- Carbon and Stainless Steel Terminal Check Valves.
- Electric Flow Monitor Switch

Drives Presently Available

- End Ratchet — 37.51
- Internal End Rotary

1:1	112.5:	600:1
3:1	120:1	800:1
37.5:1	160:1	900:1
40:1	200:1	1200:1
75:1	240:1	1600:1
80:1	300:1	1800:1
100:1	400:1	2400:1
		3600:1

- Internal Bottom Rotary

10:1	30:1	40:1	60:1
------	------	------	------

- Internal Front or Rear Rotary

10:1	30:1	40:1	60:1
------	------	------	------

- Gearhead (90 °)

10:1	40:1	180:1	360:1
30:1	60:1	270:1	540:1

- Center Rear Rotary

120:1	180:1	250:1	375:1
-------	-------	-------	-------

Technical Assistance

- Available from KLS or your local distributor listed below.

KLS Kipp
Lubrication Systems
FRED C. GILBERT CO.
1615 A BEDFORD WAY
BAKERSFIELD, CA. 93308
805-399-9569
Fax 805-393-9654

MEGA M-55

- Positive Sight Feed.
- 6000 PSI maximum pressure.
- Weatherproof construction.
- Individual removable pumping units.
- Pumping units interchangeable in McCord or Lincoln Reservoirs.
- Replacement parts for McCord and Lincoln Lubricators.
- Furnished as original equipment by most major compressor and pump manufacturers.
- A product of Kipp Lubrication Systems, manufacturers of Force Feed Lubricators since 1898.

