

Rotonics Cone Bottom Tanks

www.rototonics.com/tanks/RMIG/Cone.htm

RMI-G

- Available in Crosslink Polyethylene or FDA approved High Density Linear Polyethylene (ANSI/NSF Standard 61).
- These heavy duty tanks are used for mixing, settling, and storage of dry materials, as well as highly viscous solutions, up to 16.5 lbs./gallon.
- Basic stands are equipped with forklift channels.

- Seamless, one piece construction.
- Installed inlets and outlets are available to fit certain specifications.
- Impact and corrosion resistant.
- Optional mixer mounts and pump platforms are available.



Open Top

| Item# | Size (Gal.) | Dia. (In.) | Ht. (In.) | Ht. w/Stand (In.) | Degree of Slope |
|-------|-------------|------------|-----------|-------------------|-----------------|
| 6501 | 920 | 90 | 63 | 76 | 50 |
| 6506 | 1440 | 90 | 79 | 92 | 50 |
| 6511 | 2175 | 90 | 106 | 119 | 50 |
| 6516 | 2900 | 90 | 136 | 149 | 50 |

Dome Top

| Item# | Size (Gal.) | Dia. (In.) | Ht. w/Lid (In.) | Ht. w/Stand (In.) | Lid (In.) | Degree of Slope |
|--------|-------------|------------|-----------------|-------------------|-----------|-----------------|
| 6475 | 55 | 32 | 33 | 53 | 8/16* | 60 |
| 6485 | 115 | 32 | 51 | 71 | 8/16* | 60 |
| 6490 | 175 | 32 | 69 | 88 | 8/16* | 60 |
| 6495 | 230 | 32 | 86 | 106 | 8/16* | 60 |
| 6496 | 500 | 52 | 83 | 103 | 24 | 60 |
| 6497 | 700 | 52 | 110 | 130 | 24 | 60 |
| 6500** | 1100 | 90 | 77 | 90 | 16 | 50 |
| 6505** | 1600 | 90 | 96 | 109 | 16 | 50 |
| 6510** | 2300 | 90 | 123 | 136 | 16 | 50 |
| 6515** | 3000 | 90 | 149 | 162 | 16 | 50 |

*Larger Lid Optional

**Molded-in lifting lugs available upon request.

Slope Bottom

| Item# | Size (Gal.) | Ht. w/Lid (In.) | Ht. w/Stand (In.) | Width (In.) | Length (In.) | Lid (In.) |
|-------|-------------|-----------------|-------------------|-------------|--------------|-----------|
| 6518 | 350 | 74 | 97 | 38 | 40 | 16 |
| 6519 | 400 | 83 | 106 | 38 | 40 | 16 |

Limited Tank Warranty: RMI warrants to the original purchaser all tanks manufactured by RMI to be free from defects in material and workmanship for a period of five (5) years from date of manufacture, with the exception of D.O.T. and Septic Tanks, which have a special warranty. The Guido Tanks also have a (5) year warranty. **Review the chemical resistance guide and warranty instruction information prior to the installation and use of RMI Tanks. Hard-plumbing of tanks is not recommended due to the expansive/contractive characteristics of Polyethylene. All weights, dimensions, and gallowage markers are approximate.**

Fred C. Gilbert Co.
106 Norris Road
Bakersfield, Ca. 93308
661-399-9569
fax 661-393-9654

Quality Products and Exceptional Service