

# Rotonics Secondary Containment Basins

www.rotonics.com/tanks/RMIG/Containment.htm

## RMI-G



### Containment Basins (with Offset Flange)

Item#	Size (Gal.)	Basin Outside Dia. (In.)	Inside Dia. (In.)	Basin Ht. (In.)	Interior Tank Size (Gal.)
6548	80	33	25	27	70
6552	150	37	31	38	130
6554	275	48	38	40	200
6555	425	61	50	37	330
6559	625	61	50	53	450/550
6561	800	61	50	68	710

### Containment Basins (with Offset Flange)

- Available in Crosslink Polyethylene or FDA approved High Density Linear Polyethylene (ANSI/NSF Standard 61).
- Off center opening is designed to permit easy installation of the pump, allowing more room for connections.
- Available with an optional weather-stripping gasket which aids in reducing the amount of debris and moisture that enters the basin.
- Containment basins limit the likelihood of costly and time consuming spills, leaks, and overflows, which assists in avoiding stiff penalties from Local, State, and Federal Agencies.
- Seamless, one piece construction.
- Impact and corrosion resistant.
- Hard-plumbing of tank is not recommended due to the expansive/contractive characteristics of Polyethylene.
- Fittings and accessories installed per your specifications.

### Containment Basins (with 3" Molded-in Flange)

Item#	Size (Gal.)	Basin Outside Dia. (In.)	Inside Dia. (In.)	Basin Ht. (In.)	Interior Tank Size (Gal.)
6558	490	72	68	30	330
6560	700	72	65	42	550
6564	875	90	83	34	750
6563	960	72	65	57	600
6566	1420	90	83	54	1000
6568	1440	72	65	85	1225
6570	2090	90	83	79	1500
6574	3370	118	111	77	2500/3000
6576	5930	118	111	128	4300/5200

### Containment Basins (with 3" Molded-in Flange)

- Available in Crosslink Polyethylene or FDA approved High Density Linear Polyethylene (ANSI/NSF Standard 61).
- Containment basins limit the likelihood of costly and time consuming spills, leaks, and overflows, which assists in avoiding stiff penalties from Local, State, and Federal Agencies.
- Seamless, one piece construction.
- Impact and corrosion resistant.
- Hard-plumbing of tank is not recommended due to the expansive/contractive characteristics of Polyethylene.
- When determining size of secondary containment basins, always refer to factory drawings and local codes to confirm primary storage tank compatibility.

**Limited Tank Warranty:** RMI warrants to the original purchaser all tanks manufactured by RMI to be free from defects in material and workmanship for a period of five (5) years from date of manufacture, with the exception of D.O.T. and Septic Tanks, which have a special warranty. The Guido Tanks also have a five (5) year warranty. **Review the chemical resistance guide and warranty instruction information prior to the installation and use of RMI Tanks. Hard-plumbing of tank is not recommended due to the expansive/contractive characteristics of Polyethylene. All weights, dimensions, and gallonage markers are approximate.**

**Fred C. Gilbert Co.**  
 106 Norris Road  
 Bakersfield, Ca. 93308  
 661-399-9569  
 fax 661-393-9654

**Quality Products and Exceptional Service**