

Rotonics Vertical Freestanding Tanks

www.rotonics.com/tanks/RMIG/Vertical.htm

RMI-G

- Available in Crosslink Polyethylene or FDA approved High Density Linear Polyethylene (ANSI/NSF Standard 61).
- Extremely durable crosslink material available for critical applications.
- Vertical Tanks are available in natural, black, and various other colors upon request.
- Impact and corrosion resistant.
- UV stabilizers aid in resistance to environmental aging.
- Seamless, one piece construction.
- Fittings, valves, and fabricated accessories are also available.
- All Vertical Tanks are designed with a Heavy Duty Wall for containment of liquids up to 16.5 lbs./gal. 1225 - 6500 gallon Vertical Tanks are also available in Standard Wall for containment of liquids up to 12.5 lbs./gal.
- Tanks can be equipped with heat tracing foam insulation, which assists in maintaining thermostatically controlled uniform temperatures of tank contents.
- Heavy valves, strainers, and hoses need a secondary support to prevent applying an excessive load on tank outlets.



RMI has been a pioneer and, for the last three decades, a leading innovator in the manufacturing of all sizes of both Linear and Crosslink Polyethylene Tanks.



Item#	Size (Gal.)	Dia. (In.)	Ht. w/Lid (In.)	Lid (In.)
6316	22	20	20	8
6318	70	23	44/43	8/16 *
6320	130	29	51/50	8/16 *
6325	200	36	53/52	8/16 *
6327	250	36	65/63	8/16 *
6328	310	32	93	8/16 *
6330	330	47	53/52	8/16 *
6331	450	48	66	16
6333	500	60	51	24
6335	550	47	78	16
6340	600	72	42	16
6341	700	60	66	24
6342	710	47	105	16
6345	750	72	50	16
6350	1000	72	66	16

Item#	Size (Gal.)	Dia. (In.)	Ht. w/Lid (In.)	Lid (In.)
6356	1225	60	118	24
6351	1300	72	83	16
6358	1500	60	135	24
6360	1500	72	94	16
6386	2500	96	92/91	16/22*
6388	2900	102	92	16/22*
6390	3000	96	108/107	16/22*
6397	4000	96	141/140	16/22*
6406	4100	102	124	16/22*
6400**	4500	118	102	22
6407	4995	142	87/86	16/22*
6408	5300	102	164	16/22*
6410**	6500	118	142	22

*Larger Lid Optional

**Molded-in lifting lugs available upon request.

Limited Tank Warranty: RMI warrants to the original purchaser all tanks manufactured by RMI to be free from defects in material and workmanship for a period of five (5) years from date of manufacture, with the exception of D.O.T. and Septic Tanks, which have a special warranty. The Guido Tanks also have a five (5) year warranty.

Review the chemical resistance guide and warranty instruction information prior to the installation and use of RMI Tanks. Hard-plumbing of tank is not recommended due to the expansive/contractive characteristics of Polyethylene. All weights, dimensions, and gallonage markers are approximate.

Fred C. Gilbert Co.
106 Norris Road
Bakersfield, Ca. 93308
661-399-9569
fax 661-393-9654

Quality Products and Exceptional Service