



ROTONICS MANUFACTURING INC.

TANKS (Linear or Crosslink Polyethylene)


Rotationally Molded, Corrosion Resistant ***

*** See Chemical Resistance Guide and Warranty information

VERTICAL FREE STANDING TANKS

Size	Dia.	Ht.	w/Lid	Entry	Size	Dia.	Ht.	w/Lid	Entry	Size	Dia.	Ht.	w/Lid	Entry
18 Gal	18	21	1	8	550 Gal	53	64	15	1500 Gal	72	94	15		
** 22 Gal	20	20	8/15		550 Gal	65	45	8	* 1600 Gal	90	67	15		
** 35 Gal	19	33	8		600 Gal	72	43	15	1650 Gal	86	74	15		
65 Gal	28	36	8		710 Gal	47	103	15	2000 Gal	90	77	15		
** 70 Gal	23	42	8/15		750 Gal	72	50	15	* 2300 Gal	90	93	15		
120 Gal	32	44	8		850 Gal	68	60	15	* 2500 Gal	90	100	15		
** 130 Gal	29	47	8/15		1000 Gal	72	66	15	* 2800 Gal	102	84	24		
** 130 Gal	29	49	8/15		* 1100 Gall	90	48	15	* 3000 Gal	90	121	15		
** 175 Gal	29	65	8		1100 Gal	86	53	15	3800 Gal	118	88	22		
** 200 Gal	36	51	8/15		1150 Gal	80	63	15	* 3850 Gal	102	113	24		
300 Gal	34	82	8		1200 Gal	90	51	15	* 4300 Gal	102	126	24		
305 Gal-Slim	32	92	8		1225 Gal	60	118	24	* 4500 Gal	118	102	22		
** 330 Gal	47	51	8/15		1450 Gal	80	73	15	* 5200 Gal	102	155	24		
450 Gal	48	64	15		1500 Gal	60	135	24	* 6500 Gal	118	142	22		
525 Gal	47	79	8/15											
550 Gal	47	76	15											

- Available in natural, black, or colors upon request
- Designed for two specific gravities
- Fittings, valves, fabricated accessories available




For Additional Information Contact:
Fred C. Gilbert Company
 106 Norris Road
 Bakersfield, Ca. 93308 USA
 Telephone (661) 399-9569
 Fax (661) 393-9654

* Models available with molded-in lifting lugs ** 15" Lid optional. Tank includes overflow

GUIDO® ABOVE GROUND, FRESH WATER TANKS -GREEN ONLY

Premium Potable Water Tanks

The popular FDA approved green color blends with the environment and provides a totally opaque tank that provides additional protection from UV attack while reducing algae growth. Installation is easy due to the molded in lifting lugs (available on all models 1100 gallons and up). The tanks may be placed on any flat level "compacted" surface, a concrete pad is recommended. Installation instructions are available. All fresh water green tanks come standard with a 1 1/2" fill and 2" discharge. Optional 4" fire fittings, anti-vortex assemblies and 3" water tank vents are available.




Size	Dia.	Ht.	Entry	Size	Dia.	Ht.	Entry
330 Gal	47	51	8	2300 Gal	90	91	15
450 Gal	48	64	15	2800 Gal	102	79	24
550 Gal	47	76	15	3000 Gal	90	118	15
1000 Gal	72	64	15	3850 Gal	102	108	24
1100 Gal	90	47	15	4300 Gal	102	124	24
1500 Gal	72	92	15	4500 Gal	102	118	22
1600 Gal	90	66	15	5200 Gal	102	152	24
				6500 Gal	118	143	22

REGGY® TANKS-BLACK ONLY

Fire Protection, Potable Water & Irrigation

RMI's most economical water storage tank manufactured from virgin polyethylene that meets all FDA standards and specifications. The deep black opaque color reduces algae growth and adds further protection from the sun's UV rays. REGGY tanks are lightweight and easy to handle by rolling into place or lifting by the molded in lifting lugs. Install on a compacted level surface.


A concrete pad is recommended. Installation instructions are available. Tanks come standard with a 1 1/2" fill port and 2" discharge installed. Optional 4" fire fitting, anti-vortex assembly and 3" vent are available.



Size	Dia.	Ht.	Entry
2500 Gal	90	100	15
2800 Gal	102	79	24
3000 Gal	90	118	15
3850 Gal	102	108	24
4500 Gal	102	118	22
5200 Gal	102	152	24

HORIZONTAL LEG TANKS


Size	Dia.	Ht.	Length	Entry	Size	Dia.	Ht.	Length	Entry
25 Gal	16	18	18	6	300 Gal	37	42	64	10
55 Gal	24	28	38	10	550 Gal	50	56	74	17
110 Gal	31	35	41	10	600 Gal	48	50	85	17
200 Gal	32	37	64	10	1050 Gall	48	50	149	17



Industrial and agricultural tanks designed for transporting and sprayer applications. Polyethylene offers tremendous chemical resistance (See Chemical Resistance Guide and Warranty information) making these the perfect tank for your needs from farm chemicals, to potable water. RMI poly tanks are very durable, yet lightweight, easy to install and clean. Some horizontal tanks require tie downs or saddles, check with your sales representative.

HORIZONTAL SADDLE TANKS

Size	Dia.	Length	Entry	Size	Dia.	Length	Entry
150 Gal	30	42	10	300 Gal	38	62	10
152 Gal	32	52	10	300 Gal	38	72	10
200 Gal	33	68	8	400 Gal	42	75	10
202 Gal	32	66	10	500 Gal	48	75	10




PICK UP TRUCK TANKS

Size	Ht.	Width	Length	Entry
180 Gal	27	53	36	8
195 Gal	28	61	38	8
295 Gal	28	61	60	8
450 Gal	38	65	49	10
475 Gal	45	65	65	8




LOAF TANKS

Size	Ht.	Width	Length	Entry
50 Gal	16	26	41	8
55 Gal	14	26	41	8
100 Gal	29	26	41	8
110 Gal	26	26	41	8
200 Gal	28	36	48	8
300 Gal	29	42	62	8




LIQUID TRANSPORTER TOTES

300 Gal.



This picture denotes a 300 gallon liquid transporter. It comes with a 15" lid. Linear or Crosslink.



330 Gal.

Crosslink or Linear tank in a sturdy steel frame and skid. Four way forkliftable for easy loading and handling. These units stack two high and two across in a standard truck (height 45" | width 44" | length 52") | Sump bottom for maximum drainage with protected 2" valve, 7" threaded fill cap for easy access and cleaning. Natural polyethylene allows for liquid level viewing.



300 Gal. 'ALL POLY' Transporter


Molded from FDA approved materials for use in the cosmetic and food industries. This unit can also be manufactured from are rugged crosslink polyethylene for optimum chemical resistance. 10" threaded filler cap for easy clean out and 2" recessed valve for protection. Drainage is from the lowest level of the tank for complete product discharge. Suitable for mixing, storage and shipping of a variety of liquids.

CONTAINMENT BASINS

With Removable lids



Size	Dia.	Inside Dia.	Ht.
80 Gal	90	100	15
150 Gal	102	79	24
27.5 Gal	90	118	15
425 Gal	102	108	24
625 Gal	102	118	22
800 Gal	102	152	24




Size	Dia.	Ht.	Size	Dia.	Ht.
122 Gal	29	47	960 Gal	72	57
200 Gal	36	50	1420 Gal	90	54
300 Gal	46	49	1440 Gal	72	85
490 Gal	72	31	1800 Gal	87	50
550 Gal	53	64	2090 Gal	90	79
700 Gal	72	42	3370 Gal	118	71
850 Gal	68	60	5930 Gal	118	128
875 Gal	90	34			

OFF CENTER OPENING

This permits easy installation of the pump and allows more room for connections. 80-800 gallons basins are available with permanent or removable covers. Optional weather-stripping gasket to reduce debris and moisture from entering the basin.

Limit the liabilities of costly and time consuming spills, leaks and overflows with an RMI Secondary Containment basin. Federal, State and Local regulatory agencies have enacted stringent rules and stiff penalties for spillage or leakage from storage tanks. Install a RMI Polyethylene Containment Basin which is acid resistant, lightweight and in most cases available from stock. Sizes range from 29" to 118" in diameter to accommodate most requirements from 55 to 5200 gallons.

FITTINGS AND ACCESSORIES



FITTINGS


Compression style fittings in sizes from 1/2"-4" | Available in PVC, CPVC, Polypropylene, and 316 Stainless Steel. EPDM, Neoprene, Viton and Polyfoam Gaskets for complementing chemical compatibility with the contents of the tank. Ball valves, sight tubes, U-vents and additional plumbing fittings are available. We can suit all your fitting requirements. Call for a quote.

ACCESSORIES

Heat Tracing and foam insulation for maintaining thermostatically controlled uniform temperature of tanks contents. Individually quoted to meet your specific needs.

Platform stands flat and dish bottoms for complete drainage, available with mixer mounts and pump platforms. Forkliftable skids and custom fabrication available.

CONE BOTTOM TANKS




Open Top

Size	Dia.	Ht.	Slope
920 Gal	90	63	50
1440 Gal	90	79	50
2175 Gal	90	106	50
2900 Gal	90	136	50

These heavy duty tanks are used for mixing, settling, and storage of dry materials as well as highly viscous solutions. They are also designed to hold 16 1/2 per gallon solutions. Stands with optional mixer mounts, pump platforms and forklift channels are available. Forklift channels are standard. The large models have standard molded in lifting lugs. Installed inlets and outlets to fit your specific needs are available.

* Models available with molded-in lifting lugs


** 15" Lid optional




Domed

Size	Dia.	Ht.	Degree of Entry Slope		
55 Gal	32	32	60	**	8"/15"
115 Gal	32	50	60	**	8"/15"
175 Gal	32	68	60	**	8"/15"
230 Gal	32	85	60	**	8"/15"
500 Gal	52	80	60		24"
700 Gal	52	107	60		24"
* 1100 Gal	90	76	50		15"
* 1600 Gal	90	95	50		15"
* 2300 Gal	90	122	50		15"
* 3000 Gal	90	149	50		15"

CISTERNS & SEPTIC TANKS



1000 gal.



500 gal.

RMI Cisterns are molded from virgin FDA approved polyethylene. The septic tanks are molded from polyethylene material. They have a large 20" entry/view port, with manway risers and a sealed lid with gasket.

SEPTIC TANKS

Size	Ht.	Width	Length	Entry
500 Gal	35	69	92	20
1000 Gal	49	57	127	20

CISTERNS

Size	Ht.	Width	Length	Entry
500 Gal	35	69	92	20
1200 Gal	49	57	127	20