



# ROTONICS MANUFACTURING INC.

## TANKS (Linear or Crosslink Polyethylene)


Rotationally Molded, Corrosion Resistant \*\*\*

\*\*\* See Chemical Resistance Guide and Warranty information

### VERTICAL FREE STANDING TANKS

| Size         | Dia. | Ht. | w/Lid | Entry | Size        | Dia. | Ht. | w/Lid | Entry      | Size | Dia. | Ht. | w/Lid | Entry |
|--------------|------|-----|-------|-------|-------------|------|-----|-------|------------|------|------|-----|-------|-------|
| 18 Gal       | 18   | 21  | 2     | 1     | 550 Gal     | 53   | 64  | 15    | 1500 Gal   | 72   | 94   | 15  |       |       |
| ** 22 Gal    | 20   | 20  | 8     | 15    | 550 Gal     | 65   | 45  | 8     | * 1600 Gal | 90   | 67   | 15  |       |       |
| ** 35 Gal    | 19   | 33  | 8     |       | 600 Gal     | 72   | 43  | 15    | 1650 Gal   | 86   | 74   | 15  |       |       |
| 65 Gal       | 28   | 36  | 8     |       | 710 Gal     | 47   | 103 | 15    | 2000 Gal   | 90   | 77   | 15  |       |       |
| ** 70 Gal    | 23   | 42  | 8/15  |       | 750 Gal     | 72   | 50  | 15    | * 2300 Gal | 90   | 93   | 15  |       |       |
| 120 Gal      | 32   | 44  | 8     |       | 850 Gal     | 68   | 60  | 15    | * 2500 Gal | 90   | 100  | 15  |       |       |
| ** 130 Gal   | 29   | 47  | 8/15  |       | 1000 Gal    | 72   | 66  | 15    | * 2800 Gal | 102  | 84   | 24  |       |       |
| ** 130 Gal   | 29   | 49  | 8/15  |       | * 1100 Gall | 90   | 48  | 15    | * 3000 Gal | 90   | 121  | 15  |       |       |
| ** 175 Gal   | 29   | 65  | 8     |       | 1100 Gal    | 86   | 53  | 15    | 3800 Gal   | 118  | 88   | 22  |       |       |
| ** 200 Gal   | 36   | 51  | 8/15  |       | 1150 Gal    | 80   | 63  | 15    | * 3850 Gal | 102  | 113  | 24  |       |       |
| 300 Gal      | 34   | 82  | 8     |       | 1200 Gal    | 90   | 51  | 15    | * 4300 Gal | 102  | 126  | 24  |       |       |
| 305 Gal-Slim | 32   | 92  | 8     |       | 1225 Gal    | 60   | 118 | 24    | * 4500 Gal | 118  | 102  | 22  |       |       |
| ** 330 Gal   | 47   | 51  | 8/15  |       | 1450 Gal    | 80   | 73  | 15    | * 5200 Gal | 102  | 155  | 24  |       |       |
| 450 Gal      | 48   | 64  | 15    |       | 1500 Gal    | 60   | 135 | 24    | * 6500 Gal | 118  | 142  | 22  |       |       |
| 525 Gal      | 47   | 79  | 8/15  |       |             |      |     |       |            |      |      |     |       |       |
| 550 Gal      | 47   | 76  | 15    |       |             |      |     |       |            |      |      |     |       |       |

- Available in natural, black, or colors upon request
- Designed for two specific gravities
- Fittings, valves, fabricated accessories available




For Additional Information Contact:  
**Fred C. Gilbert Company**  
 106 Norris Road  
 Bakersfield, Ca. 93308 USA  
 Telephone (661) 399-9569  
 Fax (661) 393-9654

\* Models available with molded-in lifting lugs    \*\* 15" Lid optional.    Tank includes overflow

### GUIDO® ABOVE GROUND, FRESH WATER TANKS -GREEN ONLY

#### Premium Potable Water Tanks




The popular FDA approved green color blends with the environment and provides a totally opaque tank that provides additional protection from UV attack while reducing algae growth. Installation is easy due to the molded in lifting lugs (available on all models 1100 gallons and up). The tanks may be placed on any flat level "compacted" surface, a concrete pad is recommended. Installation instructions are available. All fresh water green tanks come standard with a 1 1/2" fill and 2" discharge. Optional 4" fire fittings, anti-vortex assemblies and 3" water tank vents are available.

| Size     | Dia. | Ht. | Entry | Size     | Dia. | Ht. | Entry |
|----------|------|-----|-------|----------|------|-----|-------|
| 330 Gal  | 47   | 51  | 8     | 2300 Gal | 90   | 91  | 15    |
| 450 Gal  | 48   | 64  | 15    | 2800 Gal | 102  | 79  | 24    |
| 550 Gal  | 47   | 76  | 15    | 3000 Gal | 90   | 118 | 15    |
| 1000 Gal | 72   | 64  | 15    | 3850 Gal | 102  | 108 | 24    |
| 1100 Gal | 90   | 47  | 15    | 4300 Gal | 102  | 124 | 24    |
| 1500 Gal | 72   | 92  | 15    | 4500 Gal | 102  | 118 | 22    |
| 1600 Gal | 90   | 66  | 15    | 5200 Gal | 102  | 152 | 24    |
|          |      |     |       | 6500 Gal | 118  | 143 | 22    |

### REGGY® TANKS-BLACK ONLY

#### Fire Protection, Potable Water & Irrigation




RMI's most economical water storage tank manufactured from virgin polyethylene that meets all FDA standards and specifications. The deep black opaque color reduces algae growth and adds further protection from the sun's UV rays. REGGY tanks are lightweight and easy to handle by rolling into place or lifting by the molded in lifting lugs. Install on a compacted level surface.

A concrete pad is recommended. Installation instructions are available. Tanks come standard with a 1 1/2" fill port and 2" discharge installed. Optional 4" fire fitting, anti-vortex assembly and 3" vent are available.


| Size     | Dia. | Ht. | Entry |
|----------|------|-----|-------|
| 2500 Gal | 90   | 100 | 15    |
| 2800 Gal | 102  | 79  | 24    |
| 3000 Gal | 90   | 118 | 15    |
| 3850 Gal | 102  | 108 | 24    |
| 4500 Gal | 102  | 118 | 22    |
| 5200 Gal | 102  | 152 | 24    |

### HORIZONTAL LEG TANKS



| Size    | Dia. | Ht. | Length | Entry | Size      | Dia. | Ht. | Length | Entry |
|---------|------|-----|--------|-------|-----------|------|-----|--------|-------|
| 25 Gal  | 16   | 18  | 18     | 6     | 300 Gal   | 37   | 42  | 64     | 10    |
| 55 Gal  | 24   | 28  | 38     | 10    | 550 Gal   | 50   | 56  | 74     | 17    |
| 110 Gal | 31   | 35  | 41     | 10    | 600 Gal   | 48   | 50  | 85     | 17    |
| 200 Gal | 32   | 37  | 64     | 10    | 1050 Gall | 48   | 50  | 149    | 17    |

### HORIZONTAL SADDLE TANKS




| Size    | Dia. | Length | Entry | Size    | Dia. | Length | Entry |
|---------|------|--------|-------|---------|------|--------|-------|
| 150 Gal | 30   | 42     | 10    | 300 Gal | 38   | 62     | 10    |
| 152 Gal | 32   | 52     | 10    | 300 Gal | 38   | 72     | 10    |
| 200 Gal | 33   | 68     | 8     | 400 Gal | 42   | 75     | 10    |
| 202 Gal | 32   | 66     | 10    | 500 Gal | 48   | 75     | 10    |

### PICK UP TRUCK TANKS



| Size    | Ht. | Width | Length | Entry |
|---------|-----|-------|--------|-------|
| 180 Gal | 27  | 53    | 36     | 8     |
| 195 Gal | 28  | 61    | 38     | 8     |
| 295 Gal | 28  | 61    | 60     | 8     |
| 450 Gal | 38  | 65    | 49     | 10    |
| 475 Gal | 45  | 65    | 65     | 8     |

### LOAF TANKS




| Size    | Ht. | Width | Length | Entry |
|---------|-----|-------|--------|-------|
| 50 Gal  | 16  | 26    | 41     | 8     |
| 55 Gal  | 14  | 26    | 41     | 8     |
| 100 Gal | 29  | 26    | 41     | 8     |
| 110 Gal | 26  | 26    | 41     | 8     |
| 200 Gal | 28  | 36    | 48     | 8     |
| 300 Gal | 29  | 42    | 62     | 8     |


Industrial and agricultural tanks designed for transporting and sprayer applications. Polyethylene offers tremendous chemical resistance (See Chemical Resistance Guide and Warranty information) making these the perfect tank for your needs from farm chemicals, to potable water. RMI poly tanks are very durable, yet lightweight, easy to install and clean. Some horizontal tanks require tie downs or saddles, check with your sales representative.

# LIQUID TRANSPORTER TOTES

300 Gal.



This picture denotes a 300 gallon liquid transporter. It comes with a 15" lid. Linear or Crosslink.



330 Gal.

Crosslink or Linear tank in a sturdy steel frame and skid. Four way forkliftable for easy loading and handling. These units stack two high and two across in a standard truck (height 45" | width 44" | length 52") | Sump bottom for maximum drainage with protected 2" valve, 7" threaded fill cap for easy access and cleaning. Natural polyethylene allows for liquid level viewing.



300 Gal. 'ALL POLY' Transporter


Molded from FDA approved materials for use in the cosmetic and food industries. This unit can also be manufactured from are rugged crosslink polyethylene for optimum chemical resistance. 10" threaded filler cap for easy clean out and 2" recessed valve for protection. Drainage is from the lowest level of the tank for complete product discharge. Suitable for mixing, storage and shipping of a variety of liquids.

## CONTAINMENT BASINS

With Removable lids



| Size     | Dia. | Inside Dia. | Ht. |
|----------|------|-------------|-----|
| 80 Gal   | 90   | 100         | 15  |
| 150 Gal  | 102  | 79          | 24  |
| 27.5 Gal | 90   | 118         | 15  |
| 425 Gal  | 102  | 108         | 24  |
| 625 Gal  | 102  | 118         | 22  |
| 800 Gal  | 102  | 152         | 24  |




| Size    | Dia. | Ht. | Size     | Dia. | Ht. |
|---------|------|-----|----------|------|-----|
| 122 Gal | 29   | 47  | 960 Gal  | 72   | 57  |
| 200 Gal | 36   | 50  | 1420 Gal | 90   | 54  |
| 300 Gal | 46   | 49  | 1440 Gal | 72   | 85  |
| 490 Gal | 72   | 31  | 1800 Gal | 87   | 50  |
| 550 Gal | 53   | 64  | 2090 Gal | 90   | 79  |
| 700 Gal | 72   | 42  | 3370 Gal | 118  | 71  |
| 850 Gal | 68   | 60  | 5930 Gal | 118  | 128 |
| 875 Gal | 90   | 34  |          |      |     |

OFF CENTER OPENING

This permits easy installation of the pump and allows more room for connections. 80-800 gallons basins are available with permanent or removable covers. Optional weather-stripping gasket to reduce debris and moisture from entering the basin.

Limit the liabilities of costly and time consuming spills, leaks and overflows with an RMI Secondary Containment basin. Federal, State and Local regulatory agencies have enacted stringent rules and stiff penalties for spillage or leakage from storage tanks. Install a RMI Polyethylene Containment Basin which is acid resistant, lightweight and in most cases available from stock. Sizes range from 29" to 118" in diameter to accommodate most requirements from 55 to 5200 gallons.

## FITTINGS AND ACCESSORIES



FITTINGS


Compression style fittings in sizes from 1/2"-4" | Available in PVC, CPVC, Polypropylene, and 316 Stainless Steel. EPDM, Neoprene, Viton and Polyfoam Gaskets for complementing chemical compatibility with the contents of the tank. Ball valves, sight tubes, U-vents and additional plumbing fittings are available. We can suit all your fitting requirements. Call for a quote.

ACCESSORIES

Heat Tracing and foam insulation for maintaining thermostatically controlled uniform temperature of tanks contents. Individually quoted to meet your specific needs.

Platform stands flat and dish bottoms for complete drainage, available with mixer mounts and pump platforms. Forkliftable skids and custom fabrication available.

## CONE BOTTOM TANKS




Open Top

| Size     | Dia. | Ht. | Slope |
|----------|------|-----|-------|
| 920 Gal  | 90   | 63  | 50    |
| 1440 Gal | 90   | 79  | 50    |
| 2175 Gal | 90   | 106 | 50    |
| 2900 Gal | 90   | 136 | 50    |

These heavy duty tanks are used for mixing, settling, and storage of dry materials as well as highly viscous solutions. They are also designed to hold 16 1/2 per gallon solutions. Stands with optional mixer mounts, pump platforms and forklift channels are available. Forklift channels are standard. The large models have standard molded in lifting lugs. Installed inlets and outlets to fit your specific needs are available.

\* Models available with molded-in lifting lugs


\*\* 15" Lid optional




Domed

| Size       | Dia. | Ht. | Degree of Entry Slope |    |        |
|------------|------|-----|-----------------------|----|--------|
| 55 Gal     | 32   | 32  | 60                    | ** | 8"/15" |
| 115 Gal    | 32   | 50  | 60                    | ** | 8"/15" |
| 175 Gal    | 32   | 68  | 60                    | ** | 8"/15" |
| 230 Gal    | 32   | 85  | 60                    | ** | 8"/15" |
| 500 Gal    | 52   | 80  | 60                    |    | 24"    |
| 700 Gal    | 52   | 107 | 60                    |    | 24"    |
| * 1100 Gal | 90   | 76  | 50                    |    | 15"    |
| * 1600 Gal | 90   | 95  | 50                    |    | 15"    |
| * 2300 Gal | 90   | 122 | 50                    |    | 15"    |
| * 3000 Gal | 90   | 149 | 50                    |    | 15"    |

## CISTERNS & SEPTIC TANKS



1000 gal.



500 gal.

RMI Cisterns are molded from virgin FDA approved polyethylene. The septic tanks are molded from polyethylene material. They have a large 20" entry/view port, with manway risers and a sealed lid with gasket.

SEPTIC TANKS

| Size     | Ht. | Width | Length | Entry |
|----------|-----|-------|--------|-------|
| 500 Gal  | 35  | 69    | 92     | 20    |
| 1000 Gal | 49  | 57    | 127    | 20    |

CISTERNS

| Size     | Ht. | Width | Length | Entry |
|----------|-----|-------|--------|-------|
| 500 Gal  | 35  | 69    | 92     | 20    |
| 1200 Gal | 49  | 57    | 127    | 20    |